



# Marine Fixed Mount Comparison Chart

## Bring It On.



	M330	M330G	M424G	M400BB	M410BB	M510BB	M510	M605
<b>Specifications</b>								
RF Output Power	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W	25 W / 1 W
AF Output Power	4.5 W	4.5 W	4 W	2 W	CommandMic® —more than 2 W Rx Hailer—more than 15 W	CommandMic® —more than 2 W Rx Hailer—more than 15 W	15 W	15 W
IP Rating	IPX7 (1 m depth/30 min)	IPX7 (1 m depth/30 min)	IPX7 (1 m depth/30 min)	IPX7 (1 m depth/30 min)	IPX7 (1 m depth/30 min)	IPX7 (1 m depth/30 min)	IP68 (1 m depth/60 min)	IPX8 (1 m depth/60 min)
Mil Spec Rating	NA	NA	NA	NA	NA	NA	810-C/D/E/F/G	810-C/D/E/F/G
<b>Features</b>								
NMEA 2000®	NA	NA	NA	NA	√	√	w/CT-M500	√
NMEA 0183®	√	√	√	√	√	√	√	√
DSC	√	√	√	√	√	√	√	√
AquaQuake™	√	√	√	√	√	√	√	√
Tag Scan / Favorite Channel	√	√	√	√	√	√	√	√
Dual/Tri-watch	√	√	√	√	√	√	√	√
Priority Scan	√	√	√	√	√	√	√	√
RX Weather Channel	√	√	√	√	√	√	√	√
GPS Antenna	NA	Supplied External	Internal Only	NA	√	√	Optional, UX-241	GNSS Antenna Included
AIS (RX)	NA	NA	NA	NA	NA	√	M510 Plus	M605 AIS
AIS (TX / RX)	MA-510TR	MA-510TR	MA-510TR	MA-510TR	MA-510TR	MA-510TR	MA-510TR	MA-510TR
Hailer/Foghorn	NA	NA	√	√ <sup>1</sup>	√ <sup>1</sup>	√ <sup>1</sup>	w/CT-M500	√
Active Noise Cancelling	NA	NA	√	√	√	√	√	√
Voice Scrambler	NA	NA	NA	NA	NA	NA	Optional	√

# Marine Fixed Mount Comparison Chart



	M330	M330G	M424G	M400BB	M410BB	M510BB	M510	M605
<b>Accessories</b>								
Removable Microphones	NA	NA	NA	✓	✓	✓	✓	✓
Rear Mic	NA	NA	NA	NA	NA	NA	HM-205RB**	HM-205RB**
Speaker Mic	Mic Only (HM-235 B/SW)	Mic Only (HM-235 B/SW)	HM-205B	NA	NA	NA	HM-205RB**	HM-205RB**
CommandMic™	NA	NA	HM-195GB / GW	HM-195B / SW	HM195GB / GW / B / SW	HM195GB / GW / B / SW	HM-195GB / GW	HM-195GB / GW
Number of CommandMic™ Capable	NA	NA	1	1	2	3	1	2 (+ RC-M600)
OPC Cables								
CommandMic™	NA	NA	OPC-1540 OPC-1541	OPC-1540 OPC-1541	OPC-1540 OPC-1542	OPC-1540 OPC-1543	OPC-1540 OPC-1541	OPC-1540 OPC-1541
Rear Mic	NA	NA	NA	NA	NA	NA	OPC-1000	OPC-1000
Remote Head	NA	NA	NA	NA	NA	NA	NA	OPC-2384
Command Head	NA	NA	NA	NA	NA	NA	NA	RC-M600
iOS/Android™ APP	NA	NA	NA	NA	NA	NA	RS-M500	NA

## NOTES

1. PA function / Manual Foghorn function only.

\*Use one of the three combinations when setting up your M605:  
M605 + three COMMANDMICS  
M605 + two COMMANDMICS + one Command Head  
M605 + two Command Heads + one COMMANDMIC

\*\*Rear mic requires OPC-1000

## CONTACT

Any questions about these specifications, please contact Technical Support.  
Call our Technical Team: Mon-Fri 4AM–5PM PST, (425) 454-8155 (Press #5)  
Or: <https://icom.custhelp.com/>